



STROCO P/N	SHELL SIZE	T THR'D UNC-3B	A (+/- .003)	B (+.015/- .015)	C (+.015/- .000)	D	E (+.020/- .020)	F (+.015/- .000)
S900DM-3	3	.112-40	0.625	0.925	0.641	.106/.166	0.325	0.300
S900DM-7	7	.112-40	0.719	1.019	0.719	.106/.166	0.419	0.300
S900DM-12	12	.112-40	0.813	1.113	0.844	.106/.166	0.513	0.300
S900DM-19	19	.112-40	0.906	1.192	0.968	.106/.166	0.620	0.286
S900DM-27	27	.112-40	0.968	1.376	1.094	.106/.166	0.560	0.408
S900DM-37	37	.112-40	1.187	1.500	1.281	.106/.166	0.874	0.313
S900DM-61	61	.112-40	1.437	1.812	1.594	.106/.166	1.062	0.375

SPECIFICATIONS

MATERIAL: Retainer- Aluminum alloy, 6061-T6 per AMS 4027, .032" (+.003/ -.003) thickness
 Nut- Self-Locking, clinch type, corrosion resistant alloy steel per AMS5640 (type 303)
 Performance per MIL-DTL-32258

FINISH: Retainer- Alodine per MIL-DTL-5541 CI 1A
 Optional- Epoxy Polyamide primer applied per MIL-PRF-23377
 Nut- Per NASM45938 with dry film lubricant applied per MIL-PRF-46010

NOTES: The A, B, C, and E dimensions are to be measured in the restrained position.
 This data sheet represents all options for this series, see ordering info page for part specifics.
 Parts to be marked with the respective S900DM-XXX part number, if there is enough space.

DIMENSIONS IN INCHES: TOLERANCES UNLESS OTHERWISE SPECIFIED: X.XX +/--.030"; X.XXX +/--.010"; ANGLES +/--.05*

DOCUMENT AND ITS CONTENTS ARE PROPRIETARY INFORMATION TO STROCO AND ITS AFFILIATES, USE WITHOUT AUTHORIZATION IS PROHIBITED.

CAGE NO. 19904	TITLE: NUT PLATE   	PART NUMBER S900DM
	DRAWING FOR INTERNAL USE ONLY	