



STROCO P/N	SHELL SIZE	T THR'D UNC-3B	"A" (+/- .003)	"B" (+.015/- .015)	"C" (+.015/- .000)	"D"
S921-8	8	.112-40	0.594	0.880	0.570	.106/.166
S921-10	10	.112-40	0.719	1.005	0.700	.106/.166
S921-12	12	.112-40	0.812	1.098	0.820	.106/.166
S921-14	14	.112-40	0.906	1.192	0.945	.106/.166
S921-16	16	.112-40	0.969	1.255	1.070	.106/.166
S921-18	18	.112-40	1.062	1.348	1.196	.106/.166
S921-20	20	.112-40	1.156	1.500	1.320	.106/.166
S921-22	22	.112-40	1.250	1.625	1.440	.106/.166
S921-24	24	.138-32	1.375	1.750	1.570	.123/.183
S921-25	25	.138-32	1.500	1.891	1.658	.123/.183

### SPECIFICATIONS

**MATERIAL:** Retainer- Aluminum alloy, 6061-T6 per AMS4027, .040" thickness  
 Nut- Self-Locking, clinch type, corrosion resistant alloy steel per AMS5640 (type 303)  
 Performance per MIL-DTL-32258

**FINISH:** Retainer- Alodine per MIL-DTL-5541 CI 1A  
 Optional- Epoxy Polyamide primer applied per MIL-PRF-23377  
 Nut- Per NASM45938 with dry film lubricant applied per MIL-PRF-46010

**NOTES:** See ordering information for additional options.  
 Parts to be marked with the respective S921-XX part number, if there is enough space.

DIMENSIONS IN INCHES: TOLERANCES UNLESS OTHERWISE SPECIFIED: X.XX +/- .030"; X.XXX +/- .010"; ANGLES +/- .05\*

DOCUMENT AND ITS CONTENTS ARE PROPRIETARY INFORMATION TO STROCO AND ITS AFFILIATES. USE WITHOUT AUTHORIZATION IS PROHIBITED.

CAGE NO. 19904	TITLE: <b>NUT PLATE</b>	PART NUMBER <b>S921-XX</b>
	  	REV D 06/09/2021
DRAWING FOR INTERNAL USE ONLY		